



Safety Data Sheet. Aluminium Rainwater Systems.

Product Name >>	Synthetic Enamel Paint - Part Ref: SC880
Hazards identification >>	Flammable & Harmful: Classification: Highly flammable Risk Phrases: Highly flammable 'P' Phrases: Do not breathe vapour or spray
First Aid Measures >>	General: In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person. Inhalation: Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped, give artificial respiration. Give nothing by mouth. If unconscious place in recovery position. Eye Contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 mins. Holding the eyelids apart, seek medical advice. Skin Contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Fire Fighting Measures >>	Extinguishing Media: Recommended: Carbon dioxide, Dry powder, Halogenated Hydrocarbons, Sand, Foam. Not to be Used: Water.
Special Instructions for Fire Fighting Personnel >>	Fire will produce dense black smoke containing hazardous products of combustion. Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water courses.
Synthetic Enamel Paint Cont >>	Handling: Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent creation of explosive or flammable mixtures and avoid vapour concs higher than the OEL (continued over)



Safety Data Sheet. Aluminium Rainwater Systems.

**Synthetic Enamel
Paint Cont**



Do not use in areas where potential sources of ignition exist.

Avoid skin and eye contact. Observe the labelled precautions. Store between 5 & 25°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking.

**Personal
Protection**



General Protection: All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

Respiratory Protection: Air fed respiratory equipment should be worn when sprayed if levels cannot be controlled below OEL's and engineering methods cannot be reasonably improved.

Hand Protection: Full physical protection is best.

Eye Protection: Eye protection designed to protect against liquid splashes should be worn.

Skin Protection: Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

Do not allow to come into contact with drains or water courses, or dispose of onto surfaces where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the control of Pollution and Environmental Protection Acts.