
# Product Data Sheet Two way parapet outlets





## **Product description**

Comprehensive range of roof, balcony and car park outlets offering market leading flow rate performance and a life expectancy of 50 years or more

- Functional life expectancy of 50+ years with minimal maintenance
- Made from marine grade aluminium for ultimate protection against corrosion, even in coastal or polluted environments
- Industry leading flow rate performance across the range
- Near zero maintenance, grates prevent debris entering the outlet
- Durable and strong, made from heavy grade cast aluminium for ultimate strength and durability
- Can be used horizontally or vertically
- Aluminium is a sustainable material, infinitely recyclable and responsibly sourced

# Physical properties

Material	Marine grade Aluminium alloy to BS EN1559:1997,
	BS EN 1676:1997 and BS EN 1706:1998

#### Flow rate performance

Codes	Horizontal I/s	Vertical I/s
DR450	2.38	7.83

# Functional Life Expectancy

Under normal UK atmospheric conditions, Marley Alutec systems if correctly installed have a life expectancy of 50 years or more. This may be marginally reduced in highly polluted or coastal areas.

**Clause:** R10/365

Product: Aluminium roof outlet

Type: Two way outlet (parapet)

Grate type: Flat grate

Manufacturer: Marley Alutec, Unit 1 (G-H), Hudson Road, Elms

Farm Industrial Estate, Bedford MK41 0LZ.

#### **Product information**

Visit www.marleyalutec.co.uk or click on the individual links below.

#### **Technical Services Department**

Marley Alutec Technical Services Department has many years' experience in assisting specifiers with all aspects or drainage design and installation. For advice, contact them on technical@marleyalutec.co.uk, 01234 344108

## **Standards**

All Marley Alutec systems are manufactured to and in excess of the appropriate BS or EN Standards. For a full list download the range brochure in the **Product information** section.



#### **Environmental**

Marley Alutec is committed to continually reducing its environmental impact and is accredited to ISO 14001:2004.



# Handling & storage

Outlets are delivered to site packaged and ready for installation. Outlets should be stored on a flat level surface and protected from mechanical damage.











ALUTEC ALUMINIUM RAINWATER SYSTEMS

## **Head office**

For general enquiries, please call **01234 359438**For technical enquiries please call **01234 344108**email: **enquiries@marleyalutec.co.uk**Fax: **01234 357199** 

Unit 1 (G-H), Viking Industrial Park, Hudson Road, Elms Farm Industrial Estate, Bedford MK41 OLZ

## **Export Division**

Aliaxis UK
Dickley Lane, Lenham, Kent, ME17 2DE
Telephone: **01622 858888** Fax: **01622 850778** 



