Product Data Sheet Traditional square & rectangular downpipe systems





Cast socketed aluminium downpipe systems suitable for both modern and traditional buildings

- 72x72, 102x76 & 102x102mm square and rectangular sizes
- Functional life expectancy of 50+ years with minimal maintenance
- 65% lighter than cast iron, making it easier and safer to handle on site
- Marine grade aluminium throughout for ultimate corrosion resistance ideal for coastal or heavily polluted areas
- Compatible with Evolve, Traditional and Aligator gutter ranges (gutter dependent)
- Aluminium is a sustainable material, infinitely recyclable and responsibly sourced

Physical properties

Material	Marine grade 6063 T5 extrusion and LM6 castings
Finish	Polyester powder coated to BS EN 12206-1:2004
Gutter compatibility	Evolve, Traditional and Aligator ranges (gutter dependent)

Flow rate performance

Flow rate performance is dependent on chosen gutter system. Please see Product Data Sheet for chosen gutter system as listed in **Physical properties** section.

Functional Life Expectancy

Marley Alutec aluminium rainwater systems have a functional lifeexpectancy of 50+ years with minimal maintenance. All products are manufactured using only marine grade aluminium and coated with external grade architectural powders.

	، م ند 		AB		
Code	Size (mm)	Nominal Length (m)	A (mm)	B (mm)	C (mm)
RSR313	72x72	3	125	151	42
RSR113	102x76	3	154	182	44
RSR413	102x102	3	154	182	56

C 🔪

Clause: Product:	R10/370 Traditional square aluminium rainwater system to BS 8530:2010
	Traditional rectangular aluminium rainwater system to BS 8530:2010
Manufacturer:	Marley Alutec, Unit 1 (G-H), Hudson Road, Elms Farm Industrial Estate, Bedford MK41 0LZ.

Product information

Visit www.marleyalutec.co.uk or click on the individual links below.

Technical Services Department

Marley Alutec Technical Services Department has many years' experience in assisting specifiers with all aspects or drainage design and installation. For advice, contact them on technical@marleyalutec.co.uk, 01234 359438

Standards

All Marley Alutec systems are manufactured to and in excess of the appropriate BS or EN Standards. For a full list download the range brochure in the **Product information** section.

Maintenance

Gutters should be periodically cleaned out and any built-up debris removed to maintain peak performance. Check all fixings are secure and take any remedial action to rectify if necessary. Leaf guards are available to fit each gutter system and are recommended for buildings close to trees, with restricted access, or areas susceptible to airborne debris. To maximise the life of the decorative paint finishes, all parts should be washed down with clean water at least every 12 months. This period would be shortened to 6 months in a marine/aggressive environment.



Product Data Sheet

Environmental

Marley Alutec is committed to continually reducing its environmental impact and is accredited to ISO 14001:2004.



Handling & storage

All gutter and pipe lengths are supplied in protective polythene sleeving and components packed in cardboard boxes. If polyester powder coated products are stored outside, cover with tarpaulin to guard against water ingress. If water becomes trapped within the polythene wrapping and left exposed to warm sunlight, it may leave permanent water stains on the paint finish.







digator RAINWATER SYSTEMS



evoke fascia, soffit & coping







Head office

For general enquiries, please call **01234 359438** For technical enquiries please call **01234 344108** email: **enquiries@marleyalutec.co.uk** Fax: **01234 357199**

Unit 1 (G-H), Viking Industrial Park, Hudson Road, Elms Farm Industrial Estate, Bedford MK41 0LZ

Export Division

Aliaxis UK Dickley Lane, Lenham, Kent, ME17 2DE Telephone: **01622 858888** Fax: **01622 850778**



/marleyalutec @marleyalutec in /company/marleyalutec marleyalutec.co.uk

an **OAliaxis** company