
Product Data Sheet Balcony outlets



Product description

Comprehensive range of roof, balcony and car park outlets offering market leading flow rate performance and a life expectancy of 50 years or more

- Functional life expectancy of 50+ years with minimal maintenance
- Made from marine grade aluminium for ultimate protection against corrosion, even in coastal or polluted environments
- Industry leading flow rate performance across the range
- Near zero maintenance, grates prevent debris entering the outlet
- Durable and strong, made from heavy grade cast aluminium for ultimate strength and durability
- Aluminium is a sustainable material, infinitely recyclable and responsibly sourced

Clause: R10/365

Product: Aluminium roof outlet

Type: Balcony outlet Grate type: Flat grate

Manufacturer: Marley Alutec, Unit 1 (G-H), Hudson Road, Elms

Farm Industrial Estate, Bedford MK41 0LZ.

Product information

Visit ${\it www.marleyalutec.co.uk}$ or click on the individual links below.

Physical properties

Material	Marine grade Aluminium alloy to BS EN1559:1997, BS EN 1676:1997 and BS EN 1706:1998
Load class	K3
Fire Classification	A2, s1-d0

Flow rate performance

Codes	Flat grate I/s	
DR360EX	4.1 l/s	
DR460EX	7.55 l/s	

Functional Life Expectancy

Under normal UK atmospheric conditions, Marley Alutec systems if correctly installed have a life expectancy of 50 years or more. This may be marginally reduced in highly polluted or coastal areas.

Technical Services Department

Marley Alutec Technical Services Department has many years' experience in assisting specifiers with all aspects or drainage design and installation. For advice, contact them on technical@marleyalutec. co.uk, 01234 344108

Standards

All Marley Alutec systems are manufactured to and in excess of the appropriate BS or EN Standards. For a full list download the range brochure in the **Product information** section.



Environmental

Marley Alutec is committed to continually reducing its environmental impact and is accredited to ISO 14001:2004.

Handling & storage

Outlets are delivered to site packaged and ready for installation. Outlets should be stored on a flat level surface and protected from mechanical damage.













Head office

For general enquiries, please call **01234 359438** For technical enquiries please call **01234 344108** email: **enquiries@marleyalutec.co.uk**

Fax: **01234 357199**

Unit 1 (G-H), Viking Industrial Park, Hudson Road, Elms Farm Industrial Estate, Bedford MK41 0LZ


Export Division


Aliaxis UK


Dickley Lane, Lenham, Kent, ME17 2DE

Telephone: **01622 858888** Fax: **01622 850778**









an **OAliaxis** company